





NEW AUTOMATED MACHINE FOR ROCK TILT TESTS

DESCRIPTION OF THE TECHNOLOGY

The **tilt test** is used in rock mechanics laboratories and rock engineering projects as a simple, sufficiently reliable and affordable technique for the determination of the basic friction angle of rocks or the friction angle of discontinuities.

In essence, it consists of placing a block of rock or other stone material on another supporting block or a test specimen on two other cylinders, and then tilting it until one fragment starts to slide over another (see Figure 1). At the moment when the displacement starts, the angle of the support plane with respect to the horizontal is measured, which is related to the basic friction angle of the rock or of the discontinuities depending on the type of sample used. This equipment can also be used for the development of physical scale models of slopes.

Up to now, the gradual tilting of the support plane has usually been carried out by manual means. In this equipment, there is no possibility to control the angular speed at which the platform is tilted, resulting in unwanted vibrations and human-induced speed variations, which decrease the efficiency of the test. In addition, the end of the test is manually controlled by the operator by pressing the stop button on the equipment or by stopping the manual rotation or thrust that generates the tilting of the platform. Therefore, the manual stop is not immediate, as the response time of a human to a stimulus is usually a few seconds, and this causes an error in the value of the angle obtained.

On the other hand, in long-travel tilt tests, a wedge or stop of different lengths is necessary to finish the test, which

MARKET APPLICATION SECTORS

also has a disadvantage for the versatility of the test, since it forces the user to have different types of wedges.

Finally, it should be noted that the existing equipment is only used to test small, lightweight specimens, which means that their structures are not designed to support large loads or large specimens.

For all these reasons, there is a clear need for a system that allows the tilt test to be carried out in all its variants, that can be used for samples of any weight or size, and that allows the development and completion of the automated test to eliminate the error introduced by the human factor.

The present invention consists of an automated tilt test machine with a steel profile reinforced structure for testing specimens and blocks of rock and other geomaterials of large dimensions and mass. It features precise tilt speed regulation by means of a variable speed drive that controls the lifting system, such as a linear actuator, thus significantly reducing unwanted vibrations and accelerations during the test. In addition, it has a system that is fully adjustable to the geometry of the test for the detection of movement and automatic stop by means of movement sensors when the specimens start to move or when a certain level of deformation is exceeded. Finally, the system is equipped with an adjustable lower specimen clamping stop that can slide along the test table to adjust it to the needs of the test (see Figure 2).

It is mainly aimed at the **Civil, Geological and Mining Engineering sector**, more specifically, companies that manufacture equipment for materials testing and control, as well as teaching and research.

TECHNICAL ADVANTAGES AND BUSINESS BENEFITS

- The reinforced structure allows the testing of large blocks (up to 750x500 mm and 100 kg).
- Significantly reduces unwanted vibrations and accelerations during the test process that can affect the test results.
- Possibility to achieve a higher platform tilting (up to about 80°).
- Automatic test stop avoids errors in the accurate estimation of the angle of existing equipment, which is stopped manually.
- The adjustable movable lower stop allows the development of full-slide tests (long travel).
- The structure is reinforced with steel profiles.







NEW AUTOMATED MACHINE FOR ROCK TILT TESTS

CURRENT STATE OF DEVELOPMENT

A prototype has been successfully tested on blocks of different characteristics.

INTELLECTUAL PROPERTY RIGHTS

This technology is protected by a **utility model application**:

- Patent title: "Máquina automatizada y reforzada de ensayo de inclinación tilt test".
- Application number: U202130607
- Application date: 25/03/2021

COLABORATION SOUGHT

The research group is looking for companies interested in acquiring this technology for **commercial exploitation** through utility model licensing agreements.

RELATED IMAGES



Figure 1: Tilt test on rock blocks

CONTACT

Area of relations with the company Research Results Transfer Service (OTRI) University of Alicante Telephone: +34 96 590 9959 Email: <u>areaempresas@ua.es</u> Web: <u>http://innoua.ua.es/</u>



Figure 2: View of the offer of hotels and other tourist accommodation in the city of Alicante.